TEXAS INSTRUMENTS



Are you looking to connect devices to the Internet of Things (IoT) at a distance greater than 25 km? Or even 100 km?

Then you are probably going to want to add Sub-1 GHz technology to your product to achieve this connection. The combination of long range, low power, software flexibility and operation on a less crowded spectrum make Sub-1 GHz technology ideal for these long-range IoT applications.

TI's Sub-1 GHz solutions, for operation in 169 MHz, 315 MHz, 433 MHz, 470MHz, 500 MHz, 868 MHz, 915 MHz and 920 MHz ISM bands, provide the longest real-world RF range with a proven distance greater than 100 km. With long distance, another requirement that is needed is robustness. Our Sub-1 GHz narrowband products provide the distance and robustness to meet any developer's needs for networks with the lowest power. This means the devices have the ability to transmit at a longer range, at the lowest power consumption, through concrete and cities without interruption from other sources.

To learn more about narrowband, long-range Sub-1 GHz technology read our three-part blog series on *Electronic Design* which covers different applications where narrowband is the de facto standard:

- 1. Why did Europe choose narrowband for long-range smart gas meters?
- 2. Why should you use long range narrowband in a smoke detector?
- 3. How long range narrowband can improve efficiency in agriculture

Additional resources related to Sub-1 GHz technology:

- Why Sub-1 GHz technology? Watch this video.
- · Read our long-range, narrowband RF communication white paper
- · Learn how Sub-1 GHz technology is diversifying the IoT in this white paper
- Watch these videos that demonstrate the range of narrowband technology:
 - Range test of CC1120 sub-1 GHz performance line
 - CC112x range test in Cape Town, can you go farther than 25k
 - More than 100 km range with no data loss using long range narrowband

Looking to get started with Sub-1 GHz, check out the below products and reference designs:

- CC1120 RF transceiver
- CC1200 RF transceiver
- CC1125 RF transceiver
- CC1190 range extender
- SimpleLink™ CC1310 wireless MCU or CC1312R wireless MCU

1

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2023, Texas Instruments Incorporated